



RG TSA-2448-1

Specification:

Shall be U.S. Range Regal Snap Thermostat Control Griddle. Model _____ with a total BTU/hr rating of _____ when used with natural or propane gas. Finish is to be stainless steel front and sides.

Standard Features:

- Stainless steel front, sides and landing ledge
- 24" (610mm) - 72" (1829mm) wide
- 14 Gauge splash guard
- Built-in front grease trough
- Large capacity, removable grease container
- Aluminized steel burners, one every 12" (305mm)
- 24,000 BTU/hr per burner
- Snap action thermostat control
- Temperature range 100°F - 450°F (32°C - 232°C)
- 110V cord/plug provided
- 1" (25mm) thick steel griddle plate
- 4" (102mm) legs with adjustable feet
- 3/4" rear gas connection w/ regulator
- One year parts and labor warranty

Optional Features:

- Stainless steel equipment stand with intermediate shelf
- Swivel casters on stand





Item #: _____
 Model: RG TSA-24 Series
 Product Name: Regal Series Snap Action
 Thermostat Control Griddle

Model #	Dimensions: In. (mm)			No. of Burners	Total BTU*	Griddle Size; In. (mm)	
	Width	Depth	Height			Width	Depth
RG TSA-2424-1	24(610)	30-1/4(768)	16-3/4(425)	2	48,000	24(610)	22(559)
RG TSA-2436-1	36(914)	30-1/4(768)	16-3/4(425)	3	72,000	36(914)	22(559)
RG TSA-2448-1	48(1219)	30-1/4(768)	16-3/4(425)	4	96,000	48(1219)	22(559)

*** Natural and Propane Gas**

Many local codes exist and it is the responsibility of the owner and installer to comply with those codes.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland/U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Shipping Information		
Model No.	Weight Lb/Kg	Cube
RG TSA-2424-1	270/122	18.0
RG TSA-2436-1	370/168	25.0
RG TSA-2448-1	441/200	33.0

Manifold Operating Pressure All Models			
Natural Gas		Propane	
"WC	Mbar	"WC	Mbar
5	12.5	10	25

